AQUA

- ✓ **Integrated Recovery**
- ✓ **Temperatures up to 120°C**
- ✓ **Integrate high quality toggle swivel**
- ✓ **Ready to use**

Mosmatic Surface Cleaner Aqua with Integrated Recovery. The dirty water is recovered and expelled with the Venturi principle eliminating the need for a vacuum system. Simply place your export hose to a desired drain point. Areas both large and small are cleaned effectively and efficiently without requiring bulky vacuum systems and long runs of hosing.





TECHNICAL DATA


Pressure	275 bar
Temperature	120°C
Inlet	G3/8" F



FL-SAR

FEATURES

Integrated recovery
The black anodized aluminum suction device collects the dirty water via the Venturi and double housing principal. Mount your export hose on the suction device and place it into the desired port to drain the water. The use of a vacuum system is no longer needed.



Rotor Arms
Can withstand up to 275 bar, are precision welded and balanced.



2w2 (2 Arms / 2 Nozzles)
Part No. 82.623 (ø250 mm)

Quality Swivel
High rpm stainless steel swivel features reinforced self lubricated stainless steel ball bearings for improved performance. The dual spring based carbide seal system, guarantees long lasting operation under tough conditions.



KDYF Toggle Swivel
Part No. 58.912

Stainless Steel Caster
Heavy duty ø60 mm casters with custom mounting brackets ensure easy maneuvering even in confined spaces.



Stainless Steel Caster
Part No. 80.943

Name	Part No.	ø	Weight	Swivel	Rotor Arm	Nozzles	HP-Gun	Casters
FL-SAR 300	**78.243**	300	5.9 kg	1x KDYF	2x 1/8" NPTF	2x 18.1503 / 1x #3*	1x	3x ø60

Accessories

Name	Part No.	Nozzles
Nozzles package	**78.983**	2x 1502 / 1x #2*

* #2 and #3 internal nozzles self recovery



Optional protection plate
See accessories for HP Cleaner

WWW.MOSMATIC.COM