Adaptor with sieve	Part No.	Weight	
IN G3/8" F, OUT G3/8" M, MC 50	**53.001**	0.06 kg	
IN G3/8" F, OUT G3/8" M, MC 200	**53.002**	0.06 kg	
IN G1/2" F, OUT G1/2" M, MC 50	**53.005**	0.06 kg	
IN G1/2" F, OUT G1/2" M, MC 200	**53.006**	0.06 kg	

MC = Mesh count

Ball Valve 2-way	Part No.	Weight	
IN G1/4" F, OUT G1/4" F	**90.066**	0.42 kg	
IN G3/8" F, OUT G3/8" F	**90.100**	0.53 kg	
IN G1/2" F, OUT G1/2" F	**90.110**	0.64 kg	

Extension fitting	Part No.	Weight	
for DR-520 roof cleaner IN G3/8" F, OUT G3/8" M	**38217**	0.05 kg	

Extension for surface cleaner	Part No.	Weight	
440 mm, stainless IN M22x1.5 F, OUT G1/4" M	**78.908**	0.3 kg	

Hand grip replacement kit	Part No.	Weight	
for Surface Cleaner ø200/300	**78.945**	0.2 kg	

Height adjusters long	Part No.	Weight	
for DR-520 roof cleaner	**904.351**	0.2 kg	

High pressure filter	Part No.	Weight	
IN G1/4" F, OUT R1/4" M	**90.060**	0.2 kg	
IN G3/8" F, OUT G3/8" M	**90.062**	0.25 kg	

HP Quick connect coupler stainless steel, 350 bar	Part No.	Weight	
G1/4" F, D 12, NW 6, SW 22	**70.010**	0.06 kg	
G1/4" M, D 12, NW 6, SW 22	**70.011**	0.08 kg	
G3/8" F, D 15, NW 9, SW 24	**70.012**	0.1 kg	
G3/8" M, D 15, NW 9, SW 24	**70.013**	0.1 kg	

HP Quick connect plug stainless steel, 350 bar	Part No.	Weight	
G1/4" F, D 12, NW 6, SW 17	**70.020**	0.03 kg	
G1/4" M, D 12, NW 6, SW 17	**70.021**	0.03 kg	
G3/8" F, D 15, NW 9, SW 22	**70.022**	0.06 kg	
G3/8" M, D 15, NW 9, SW 22	**70.023**	0.06 kg	

Mosmatic HP Gun «NEO»	Part No.	Weight	
350 bar, 150°C, Low Trigger Force IN G3/8" F, OUT G1/4" F	**29.094**	0.6 kg	
500 bar, 150°C, Low Trigger Force IN G3/8" F, OUT G1/4" F	**29.104**	0.6 kg	

More products see HP Gun page.

Nozzle guard	Part No.	Weight	
plug on ø16 & G3/8"	**29.010**	0.01 kg	

More products upon request.

Nozzles	Part No.	Weight	
Nozzle package #2 for AQUA surface cleaner	**78.983**	0.04 kg	
Low pressure upgrade kit for Hurricane-Series	**80.9011**	3.8 kg	
Gum remover nozzle, IN G1/4" F Size #3	**29.102**	0.6 kg	
Gum remover nozzle, IN G1/4" F Size #4	**29.103**	0.6 kg	
Gum remover nozzle, IN G1/4" F Size #5	**29.119**	0.6 kg	
Ceramic nozzle, 80° angle Size 180 (040), IN G3/8" F	**29.076**	0.02 kg	

Pedal switch	Part No.	Weight	
for DR-520 roof cleaner IN M22x1.5 M, OUT M22x1.5 F	**80.987**	14.0 kg	

Prop stand	Part No.	Weight	
for HURF-300, 90 mm	**78.9012**	0.1 kg	

Protection plate for duct cleaner	Part No.	Weight	
for ø300, stainless	**901.022**	0.7 kg	
for ø400, stainless	**901.023**	1.3 kg	
for ø500, stainless	**901.024**	2.1 kg	
for ø600, stainless	**901.025**	3.0 kg	
Screw-set	**81.942**	0.05 kg	

Protection plate for surface cleaner	Part No.	Weight	
for ø200	**902.922**	0.16 kg	
for ø300	**905.378**	0.44 kg	
for ø410	**906.088**	1.07 kg	
for ø520	**905.557**	1.68 kg	
for ø750	**906.089**	3.97 kg	

Quick connection	Part No.	Weight	
IN M22x1.5 F, OUT 6 (1/4"), NW 4	**50.131**	0.07 kg	
IN M22x1.5 F, OUT 8 (5/16"), NW 5.8	**50.132**	0.07 kg	
IN M22x1.5 F, OUT 10 (3/8"), NW 7	**50.133**	0.06 kg	

Stabilizer Nozzle	Part No.	Weight	
1/4" NPTM, 95 mm	**14.901**	0.1 kg	
1/8" NPTM, 93 mm	**14.902**	0.1 kg	
1/8" NPTM, 68 mm	**14.935**	0.1 kg	
1/4" NPTM, 70 mm	**14.939**	0.1 kg	
Quick connect plug-ø12, 103 mm	**14.940**	0.1 kg	
1/4" NPTF, 95 mm	**14.943**	0.1 kg	
1/4" NPTF, 68 mm	**14.945**	0.1 kg	

Swivel for paint spray guns	Part No.	Weight	
IN G1/4" F, OUT G1/4" M	**32.916**	0.43 kg	
IN G1/8" F, OUT G1/8" M	**32.918**	0.43 kg	

Toggle joint 275 bar, 120°C	Part No.	Weight	
IN G1/4" F, OUT G1/4" F, NW 4	**42.001**	0.24 kg	
IN G1/4" F, OUT G1/8" F, NW 5	**42.906**	0.15 kg	
IN G1/4" F, OUT G1/4" F, NW 5	**42.907**	0.15 kg	

TYR Hook	Part No.	Weight	
stabilize your Duct Cleaner	**81.905**	0.1 kg	

TYR Mobile (adjustable)	Part No.	Weight	
for ø150-300 pipe	**81.911**	4.1 kg	
for ø300-500 pipe	**81.902**	4.3 kg	
for ø500-600 pipe	**81.903**	7.0 kg	

Duct Cleaner not included.

WWW.MOSMATIC.COM

Legend

M.. = metric thrust, **..M** = male, **F** = female, **G** = gas pipe thrust, **R** = gas pipe thrust conival, **QV** = quick connects, **SV** = profile ring fitting
D = diameter, **L** = length, **NW** = nominal width, **SW** = wrench size, **IN** = media input, **OUT** = media output, **RS** = basic position