ROOF CLEANER

- ✓ **Height and width adjustable**
- ✓ **Quad bearing swivel**
- ✓ **For professional roof cleaners**

The industrial-quality roof cleaner can be used quickly and efficiently while the operator remains safely on the ridge. Security, stability as well as cleaning results are emphasized. This stainless steel unit will provide optimal performance under harsh conditions. Deck height and wheel width are adjustable giving you an advantage when cleaning different styled roofs.





TECHNICAL DATA


Pressure	275 / 500 bar
Temperature	120°C
Inlet	M22x1.5-M G1/4" F




DR-520

FEATURES

Height and width adjustable
The DR-520. Width is adjustable up to 90 mm and 33 mm in height. Will work for most roof designs adding safety and stability.



Safety Eye
Allows you to easily secure the roof cleaner with a safety rope or cable.



Pressure Gauge
Use the pressure gauge to monitor your cleaning pressure. This allows you to ensure proper pressure when cleaning a variety of roofing materials.

Part. No. 903.032



Ball Valve
Makes it easy and convenient to turn off the flow to the unit.

Part. No. 90.066



Rotor Arms
Can withstand up to 275 bar or 500 bar, are precision welded and balanced.



2cw2 (2 Arms / 2 Nozzles / 275 bar)
Part No. 82.942 1/8" (ø470 mm)
Part No. 82.975 1/4" (ø470 mm)

2cw2 (2 Arms / 2 Nozzles / 500 bar)
Part No. 82.941 1/4" (ø470 mm)

Quality Swivel
High rpm stainless steel swivel features 4x reinforced self lubricated stainless steel ball bearings for improved performance. The dual spring based carbide seal system, guarantees long lasting operation under tough conditions.



DYU Swivel (500 bar)
Part No. 59.916

DYT Swivel (350 bar)
Part No. 59.907

Name	Part No.	ø	Width	Height	Weight	Rotor Arm	HP-Nozzles
DR-520	**80.651**	520	550-640	195-228	14.5 kg	2x 1/8" NPTF	---
DR-520*	**80.662**	520	550-640	195-228	14.5 kg	2x 1/8" NPTF	---

* Pressure: 500 Bar / Inlet G1/4" F

Height adjusters long
Add an additional 60 mm height if needed. e.g. for corrugated roofs.

Part No. 904.351 (1 pcs)
Requires 4 pieces



Pedal switch
For additional safety, Mosmatic recommends you turn your flow on and off using the optional pedal switch.

Part No. 80.987



WWW.MOSMATIC.COM