DOCUMENTATION TECHNIQUE

Têtes de lavage et équipements de nettoyage

Caractéristiques, plans et instructions du fabricant.
Pour le choix de votre équipement et la préparation d'une demande de devis.

GEDO FRANCE

04 85 88 02 75

tete@gedo.fr

tetelavage.gedo.fr

565 avenue du Prado - 13008 Marseille - France

tecomec
WORK BETTER

Cleaning

TK SELF SPINNING HEADS HYDROKINETIC



NEW
2026

A00 | **EN**

The Group

Tecomec is based in Reggio Emilia, the cradle of farming and industrial development, and a region renowned worldwide for its top quality technology.

As part of the **Emak Group**, today Tecomec represents one of the major production centers of components and accessories for forestry, gardening, agriculture, cleaning and industrial applications.

Tecomec's divisions are:

Forestry
Forestry equipment & saw chain care and maintenance.

Gardening
Accessories and components for garden care.

Agriculture
Accessories and components for orchard and crop sprayers.

Cleaning
Accessories and components for high pressure washing and car-wash.

A Global Presence

The Tecomec Group reaches Its customers thanks to a global and strategic presence consisting of production and distribution plants located in different countries:

- **Tecomec**, headquarter specialized in the production and distribution of components and accessories for the European market.
- **Speed Group**, producer of polyamide lines for garden and industrial uses.
- **Ningbo Tecomec Manufacturing**, producer of parts and accessories distributed by Tecomec.
- **Spraycom**, active In the wholesale trade of farming components and accessories In the Brazilian market
- **Agres**, specialises in the design and manufacture of electronic components used in precision farming.
- **Markusson**, specialized in production of professional robotic sharpeners for chainsaw chains.
- **PNR Company**, specialized in production and distribution of spray nozzles and components for industrial applications.



The Cleaning Division

tecomec WORK BETTER Cleaning

The product range includes **valves, guns, nozzles, rotating heads**, and accessories for high-pressure cleaners and cleaning systems, designed for applications such as **car wash, high-pressure cleaning, industrial, domestic and sanitazing uses.**

This line covers both the **professional** and **semi-professional** segments, serving manufacturers and distributors worldwide.

Our Offer

- **WIDE PRODUCT RANGE**
- **MORE THAN 6000 DIFFERENT ITEMS ALWAYS IN STOCK**
- **CO-DESIGN ENGINEERING CAPABILITIES**
- **GLOBAL FOOTPRINT**
- **VERTICAL PROCESS**
- **CERTIFIED PRODUCTS EXEEDING MARKET STANDARDS**



Our Brands

Today, Tecomec's Cleaning Division offers complete solutions for **high-pressure cleaning**, **sanitation**, and **industrial cleaning**.
Tecomec has consolidated experience in industrial high pressure cleaning and car wash, while **PNR** specializes in the design, production, and distribution of spray nozzles and components for industrial applications (metallurgical, paper, chemical, pharmaceutical, and food industries).

PRECISION AND POWER,
FOR EVERY CLEANING NEED.

tecomec

Design, production, and distribution of accessories and components for high-pressure cleaning and Car-Wash



tecomec.com

PNR

Design, production, and distribution of spray nozzles and components for industrial applications.



www.pnr.eu

SERIES TK

Hydrokinetic self-rotating heads
for cleaning containers and surfaces





TK1 A

20÷60 l/min

360° volumetric cleaning

Nozzles: 2 - 4 | 10÷250 bar | 20÷30 rpm



TK1 B

50÷200 l/min

360° volumetric cleaning

Nozzles: 2 - 4 | 10÷250 bar | 20÷30 rpm



TK2

20÷60 l/min

240° sectorial volumetric cleaning

Nozzles: 2 - 3 - 4 | 10÷250 bar | 90÷110 rpm



TK3

Ø 60mm | 10÷30 l/min

360° volumetric cleaning

Nozzles: 2 - 4 | 10÷250 bar | 25÷35 rpm




TK4

20÷60 l/min

FRONTAL cleaning 20°÷120°

Nozzles: 2 - 4 | 10÷250 bar | 90÷110 rpm

MAINTENANCE SIMPLE AND INTUITIVE



- Fast diagnostics and repairs.
- Easy disassembly and part replacement.
- Spare parts kits for enhanced durability.
- Multilingual manuals.

FEATURES

- Heads **calibrated** for specific flow rates and pressures.
- **High washing efficiency (95%),** ensured by **minimal pressure drop.**
- **Number and type of nozzles** can be configured **based on flow/pressure** and application type.
- **Compatible nozzles:** straight and fan-shaped.
- **Universal Compatibility.**
- **Installation:** heads can operate in any position.
- **Detergent use:** heads are compatible with cleaning agents, including the most aggressive ones.
- The heads are supplied with **EPDM seals. Viton, NBR, and others are available upon request.**

ADVANTAGES

Savings and sustainability
Reduced consumption of water, chemicals and work.

Efficiency and safety
Effective and reliable cleaning.
Compact, robust, and safe design.

Customization
Custom versions available upon request.

CERTIFICATIONS

ATEX
Heads ATEX-certified for use in explosive environments.

MOCA
Heads MOCA-certified for use in food and pharmaceutical environments.

APPLICATIONS



TRANSPORTATION

Cleaning tank truck (food, chemical, cosmetics industries, etc.)

TK1 A



TK1 B





SILOS

Cleaning silos of all sizes and industries (winemaking, food, chemical, pharmaceutical, etc.)



BIN WASHER

Washing and sanitizing urban waste vehicles

TK2



TK3



IBC & SMALL CONTAINERS

Cleaning of closed containers such as IBCs, with small access openings (for food, chemical, agricultural, industrial use, etc.)





CAR-WASH

Portals for high-pressure, no-touch vehicle washing. Surface cleaning for conveyor belts.

TK4



TK1 A

SELF SPINNING HEADS

20÷60 l/min

360° volumetric cleaning



TK1 B

SELF SPINNING HEADS

50÷200 l/min

360° volumetric cleaning



TYPE	OPERATING FLOW RATE l/min	OPERATING FLOW RATE USGpm	COMPLETE CYCLE Rotations	COMPLETE CYCLE TIME	INLET	WEIGHT kg	WEIGHT oz
TK1 A	20 MIN 60 MAX	5.3 MIN 15.85 MAX	60	2' 30"	G 1" F or NPT 1" F	8,1	285,7
TK1 B	50 MIN 200 MAX	13,2 MIN 52,8 MAX	60	2' 30"	G 1" F or NPT 1" F	8,1	285,7

Fill out the form to define the technical specifications of the product

OPERATING PRESSURE	10 bar	MIN	1 MPa		145 psi	MIN
	250 bar	MAX	25 MPa		3630 psi	MAX
TEMPERATURE	0 °C	MIN	32 °F	MIN		
	90 °C	MAX	194 °F	MAX		
NUMBER OF ROTATIONS	20 rpm	MIN				
	30 rpm	MAX				
NOZZLE CONNECTION	1/4" NPT					
MATERIAL	AISI 316 Stainless Steel-PEEK Plastic					
SEAL MATERIAL	EPDM					


Made in Italy

ON REQUEST, O-RING IN VITON® OR NBR




SUPPLIED COMPLETE WITH INLET FILTER 32 MESH (600 MICRON)

DIMENSIONS



NUMBER OF NOZZLES






TK2

SELF SPINNING HEADS

20÷60 l/min

240° sectorial volumetric cleaning





TYPE	OPERATING FLOW RATE l/min	OPERATING FLOW RATE USGpm	COMPLETE CYCLE Rotations	COMPLETE CYCLE TIME	INLET	WEIGHT kg	WEIGHT oz
TK2	20 MIN 60 MAX	5.3 MIN 15.85 MAX	30	18"	G 1/2" F or NPT 1/2" F	6,2	219,0

Fill out the form to define the technical specifications of the product

OPERATING PRESSURE	10 bar	MIN	1 MPa		145 psi	MIN
	250 bar	MAX	25 MPa		3630 psi	MAX
TEMPERATURE	0 °C	MIN	32 °F	MIN		
	90 °C	MAX	194 °F	MAX		
NUMBER OF ROTATIONS	90 rpm	MIN				
	110 rpm	MAX				
NOZZLE CONNECTION	1/8" NPT					
MATERIAL	AISI 316 Stainless Steel-PEEK Plastic					
SEAL MATERIAL	EPDM					


Made in Italy

ON REQUEST, O-RING IN VITON® OR NBR





SUPPLIED COMPLETE WITH INLET FILTER 32 MESH (600 MICRON)

DIMENSIONS



NUMBER OF NOZZLES






TK3

SELF SPINNING HEADS

10÷30 l/min

360° volumetric cleaning





TYPE	OPERATING FLOW RATE l/min	OPERATING FLOW RATE USGpm	COMPLETE CYCLE Rotations	COMPLETE CYCLE TIME	INLET	WEIGHT kg	WEIGHT oz
TK3	10 MIN 30 MAX	2.64 MIN 7.92 MAX	40	1' 36"	G 1/2 F or NPT 1/2" F	2,4	82,9

Fill out the form to define the technical specifications of the product

OPERATING PRESSURE	10 bar	MIN	1 MPa		145 psi	MIN
	250 bar	MAX	25 MPa		3630 psi	MAX
TEMPERATURE	0 °C	MIN	32 °F	MIN		
	90 °C	MAX	194 °F	MAX		
NUMBER OF ROTATIONS	25 rpm	MIN				
	35 rpm	MAX				
NOZZLE CONNECTION	M4					
MATERIAL	AISI 316 Stainless Steel-PEEK Plastic					
SEAL MATERIAL	EPDM					


Made in Italy

ON REQUEST, O-RING IN VITON® OR NBR




SUPPLIED COMPLETE WITH INLET FILTER 32 MESH (600 MICRON)

DIMENSIONS



NUMBER OF NOZZLES






TK4

SELF SPINNING HEADS

20÷60 l/min

Frontal cleaning

20°÷120°





TYPE	OPERATING FLOW RATE		INLET	WEIGHT	
	l/min	USGpm		kg	oz
TK4	20 MIN 60 MAX	5.3 MIN 15.85 MAX	G 1/2 F or NPT 1/2" F	5,7	201,1

Fill out the form to define the technical specifications of the product

OPERATING PRESSURE	10 bar	MIN	1 MPa		145 psi	MIN
	250 bar	MAX	25 MPa		3630 psi	MAX
TEMPERATURE	0 °C	MIN	32 °F	MIN		
	90 °C	MAX	194 °F	MAX		
NUMBER OF ROTATIONS	90 rpm	MIN				
	110 rpm	MAX				
NOZZLE CONNECTION	1/8" NPT					
MATERIAL	AISI 316 Stainless Steel-PEEK Plastic					
SEAL MATERIAL	EPDM					


Made in Italy

ON REQUEST, O-RING IN VITON® OR NBR




SUPPLIED COMPLETE WITH INLET FILTER 32 MESH (600 MICRON)

DIMENSIONS



SPRAY ANGLE




n° nozzles: min 2 - max 4



tecomec®

WORK BETTER

Strada della Mirandola, 11
42124 Reggio Emilia - ITALY
TEL +39 0522 959001
salesdept@tecomec.com
WWW.TECOMEC.COM



P00802075_R01 02/2026