
Rotating cleaning nozzle PicoWhirly
Series 500.234

Features:

- Cleaning with rotating solid jet
- Compact design for confined spaces
- Suitable for very high temperatures
- Made completely of stainless steel



FDA



Series 500.234

Male thread

Max. tank diameter [m]: 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

Cleaning efficiency class
2

Max. temperature
200 °C

Installation
Operation in every direction is possible

Bearing
Kolsterised slide bearing

Material
Stainless steel 316L

Recommended operating pressure
3 bar

Filtration
Line strainer with a mesh size of 0.3 mm/50 mesh

Function video
www.lechler.com/de-en/medialibrary/videos-general-industry
Or scan the QR code.

Spray angle	Ordering no. / Type	Narrowest free cross section Ø [mm]	V̇ water [l/min] p [bar] (p_{max} = 5 bar)					Max. tank diameter [m]
			1.0	2.0	**3.0**	5.0	at 40 psi [US gal/min]	
300°	**500.234.G9.00**	1.8	5.7	8.0	**9.8**	12.7	2.5	0.9

The maximum tank diameter applies to the recommended operating pressure and is meant as a recommendation only.
The cleaning result is also affected by the type of soiling.

Compressed air should be used for dry blowing for a short time only. Operation above the recommended operating pressure has a negative impact on the cleaning result and wear.

CONTACT: Lechler GmbH · Ulmer Strasse 128 · 72555 Metzingen, Germany · Phone +49 7123 962-0 · ind@lechler.de · www.lechler.com

GEDO
Distribution et conseil : GEDO FRANCE
04 85 88 02 75 | tete@gedo.fr | tetelavage.gedo.fr
565 avenue du Prado - 13008 Marseille - France