ADJUSTABLE FLANGES FOR TANK CLEANERS FEATURES AND BENEFITS

- Maximize cleaning effectiveness by positioning nozzle turret to clean around obstructions or targeting skim lines or other areas requiring extra impact
  - – Standard adjustable flanges allow positioning the nozzles at various depths along the length of the extension
  - – Adjustable ball swivel flanges allow adjustment of the spray head by as much as 60°
- Choice of connections: tri-clamp fitting, three-prong flange, 150# flange connection
- Can be used with TankJet AA090 and AA190 tank cleaners

FLANGE OPTIONS



39205 Adjustable Sanitary Flange

- Choice of 2-1/2", 3", 4" or 6" tri-clamp fittings



22250 Three-Prong Adjustable Flange



46395 Raised Face Adjustable Flange

- Choice of 2", 3" or 4" 150# raised face flanges



43047 Ball Swivel Adjustable Flange

- Choose 4" or 6" 150# adjustable ball swivel flanges. 4" sanitary version also available

DIMENSIONS AND WEIGHTS

Flange Type	Model	Flange Size	Length in. (mm)	Outside Diameter in. (mm)	Weight lbs (kg)
Adjustable Sanitary Flange for Tanks with Tri-Clamp Fitting	39205	2-1/2	4.75 (121)	3 (76)	2 (.9)
	39205	3		3.6 (91)	2.1 (.95)
	39205	4		4.7 (119)	2.5 (1.1)
	39205	6		6.6 (168)	5.3 (2.4)
Adjustable Three-Prong Flange	22250	-	4.06 (103)	5 (127)	2.8 (1.3)
Adjustable Flange for Tanks with 150# Connections	46395	2	4.81 (122)	6 (152)	12 (5.4)
	46395	3	4.94 (125)	7.5 (191)	12.9 (5.9)
	46395	6	5 (127)	9 (229)	17.7 (8.0)
Ball Swivel Adjustable Flange	43047	4	6.75 (172)	9 (229)	20 (9.1)
	43047	6		11 (279)	30 (13.6)

ORDERING INFORMATION

ADJUSTABLE FLANGES FOR TANK CLEANERS

Model – Flange Size* – Material Code

EXAMPLE: **39205** – **3** – **316SS**

*Leave blank when ordering a Three-Prong Flange.

GEDO
Distribution et conseil : GEDO FRANCE
04 85 88 02 75 | tete@gedo.fr | tetelavage.gedo.fr
565 avenue du Prado - 13008 Marseille - France

ADAPTERS AND MOUNTING KITS
FEATURES AND BENEFITS

- Adapters and kits come in many sizes and configurations to ensure the proper fit for various tanks and vessels
- A wide array of materials are available that can handle applications ranging from chemical to sanitary

ADAPTERS AND MOUNTING KIT OPTIONS



Manway Adapter

- Includes vent for vapor release, shield to prevent liquid from spraying into vent and removable plug that allows cone to be filled with liquid if additional weight is desired
- Tapered manway adapter enables drop-in-place installation of the TankJet 65, 80 or 360 with tanker truck openings between 17" and 21" (432 and 533 mm); 304 stainless steel construction, 1-1/2" NPT(M) or 2" NPT(M) available



Adapter for TankJet AA090 and AA190 Tank Cleaners

- Has a 6.25" OD, Celcon® construction with 304 stainless steel screws
- Chemically-resistant adapter enables any air or electric TankJet AA090 or AA190 tank cleaner to be used in tanks with inlet sizes ranging from 2" to 4"



Mounting Kit

- Includes everything you need – flange, lock washers, bolts and gasket
- Simplify mounting the standard TankJet AA090 or AA190 three-prong flange to a 4" or 6" 150# flange. Kit includes a 316 stainless steel raised face flange, stainless steel lock washers, bolts and PTFE gasket

DIMENSIONS AND WEIGHTS

Item	Model	Length in. (mm)	Outside Diameter in. (mm)	Weight lbs (kg)
Tapered Manway with 1-1/2" NPT(M) or 2" NPT(M) Both Ends	46573	46 (1,168)	22 (559)	75 (34)
	46579-2	46 (1.168)	22 (559)	75 (34)
Adapter	45260	3.85 (98)	6.25 (159)	1 (.45)
Mounting Kit	39204-4	.94 (24)	9 (229)	15 (6.8)
	39204-6	1.0 (25.4)	11 (279)	24 (10.9)

ORDERING INFORMATION

ADAPTERS

Model – Material Code

EXAMPLE: **45260** – **CE**

MOUNTING KITS

Model – Flange Size – Material Code

EXAMPLE: **39204** – **4** – **316SS**

GEDO

Distribution et conseil : GEDO FRANCE
04 85 88 02 75 | tete@gedo.fr | tetelavage.gedo.fr
565 avenue du Prado - 13008 Marseille - France