DOCUMENTATION TECHNIQUE

Têtes de lavage et équipements de nettoyage

Caractéristiques, plans et instructions du fabricant.
Pour le choix de votre équipement et la préparation d'une demande de devis.

GEDO FRANCE

04 85 88 02 75

tete@gedo.fr

tetelavage.gedo.fr

565 avenue du Prado - 13008 Marseille - France

ST-2320 Spray gun with adjustable nozzle ST-51.1

The choice of perfection



Nozzle-Twist: The jet can be changed from a conical, wide spray jet to a long-distance pencil jet.

Spray gun with adjustable nozzle ST-51.1

- Maximum pressure: 150 bar
- Maximum temperature: 150 °C
- Maximum flow: 80 l/min
- Internal parts of the surge nozzle are made entirely of stainless steel.
- Spray gun with adjustable nozzle made of food-safe plastic.
- Change the shape of the jet by simply turning the adjustable nozzle.

How the ST-2320 works with adjustable nozzle



Conical spray jet



Long-range pencil jet

Spray gun:	ST-2320
Max. pressure	150 bar
Max. flow	80 l/min
Max. temperature	150 °C
Inlet	rear
Swivel at inlet	standard



Swivel: inlet equipped with rotating 1/2″ female thread.

new





R+M Nr.	Pressure	Temperature	Flow	Inlet
200 051 700	150 bar	100 °C	80 l/min	3/8″ M
200 051 750	150 bar	100 °C	80 l/min	1/2″ M

new



R+M Nr.	Outlet	Inlet
202 320 567	Nozzle ST-51.1	1/2″ F swivel

www.rm-suttner.com