DOCUMENTATION TECHNIQUE

Têtes de lavage et équipements de nettoyage

Caractéristiques, plans et instructions du fabricant.
Pour le choix de votre équipement et la préparation d'une demande de devis.

GEDO FRANCE

04 85 88 02 75

tete@gedo.fr

tetelavage.gedo.fr

565 avenue du Prado - 13008 Marseille - France

TANKJET® 23240 TANK CLEANING NOZZLE

TANKJET 23240 TANK CLEANING NOZZLE FEATURES AND BENEFITS

- Compact, fluid-driven, rotating nozzles efficiently rinse vessels
- Two flat sprays produce the self-rotating force and side sprays; an optional third spray at the end of the nozzle, provides nearly full spherical coverage
- Long-wearing materials extend service life and enable operation at high temperatures
- Available in electro-polish finish or stainless steel
- Wall mount options available



TankJet 23240-3
tank cleaning nozzle



TankJet 23240-2
tank cleaning nozzle

R
RINSING

SPRAY COVERAGE
2 Side Spray



3 360°



MOUNTING OPTIONS
Vertical

SPECIFICATIONS


TankJet 23240 Tank Cleaning Nozzle	
Max. tank diameter:	3 ft. (0.9 m)
Operating principle:	Fluid-driven reactionary force
Flow rate:	3.5 to 22 gpm (14.0 to 79 lpm)
Operating pressure:	20 to 200 psi (1.4 to 13.8 bar)
Max. temperature:	350°F (177°C)
Materials:	316 stainless steel, hardened stainless steel and 50% stainless steel filled PTFE (316SS)
Inlet connection:	1/2" NPT or BSPT (F)
Optional accessories:	Strainers, recommended mesh size: 200 (74 microns) See page G2

IDEAL FOR CLEANING:

- Barrels
- Cylinders
- Ducts
- Kegs
- Pipes
- Tube

DIMENSIONS AND WEIGHTS

Model	L in. (mm)	W in. (mm)	Min. Tank Opening in. (mm)	Weight oz. (kg)
23240	3.5 (89)	1 (25.4)	1.03 (26)	8.0 (0.23)



PERFORMANCE DATA

Model	Coverage Type	Capacity Size	Liquid Flow Capacity gpm (lpm)							
			20 psi (1.4 bar)	40 psi (2.8 bar)	60 psi (4.1 bar)	80 psi (5.5 bar)	100 psi (6.9 bar)	120 psi (8.3 bar)	150 psi (10.3 bar)	200 psi (13.8 bar)
23240	2	5	3.5 (14.0)	5.0 (19.7)	6.1 (23)	7.1 (25)	7.9 (28)	8.7 (32)	9.7 (36)	11.2 (39)
		8	5.7 (22)	8.0 (32)	9.8 (36)	11.3 (41)	12.6 (45)	13.9 (52)	15.5 (58)	17.9 (63)
	3	5.7	4.0 (15.9)	5.7 (22)	7.0 (26)	8.1 (29)	9.0 (32)	9.9 (37)	11.0 (41)	12.7 (45)
		7	4.9 (19.5)	7.0 (28)	8.6 (32)	9.9 (36)	11.1 (39)	12.1 (45)	13.6 (50)	15.7 (55)
		10	7.1 (28)	10.0 (39)	12.2 (46)	14.1 (51)	15.8 (56)	17.3 (64)	19.4 (72)	22 (79)

ORDERING INFORMATION

TANKJET 23240 TANK CLEANING NOZZLE

Model* – Spray Coverage – Bearings and Races Material Code** – Capacity Size – Body Material Code

EXAMPLE: **23240** – **2** – **316SS** – **5** – **316SS**

*Add B prior to the Model type for BSPT connections.

**All bearings and races specify 316SS for Stainless Steel Type 316 (DIN 1.4571).